FC9000 SERIES BLADES

	CB09UB	Angle: 45° Diameter 0.9mm	Standard blade for vinyl cutting & self-adhesive marking film (PVC film) up to 0.25 mm thick. Maximum cutting distance is approx. 13,123 ft.
	CB09UB-K60	Angle: 30° Diameter 0.9mm	Supersteel Blade for cutting the window tint film or thin film, up to 0.25 mm thick.
	CB15U	Angle: 45° Diameter 1.5mm	Supersteel blade for cutting rigid or thicker media, 0.25 mm to 0.5 mm thick. (laminates, smart device, device screen protection media)
	CB15U-K30	Angle: 60° Diameter 1.5mm	Supersteel Blade for cutting rigid media, 0.25 mm to 0.5 mm thick. And also small detailed characters on marking film (up to 0.25mm). Recommended blade for sandblast rubber resist media cutting and Avery Series of Reflective sheeting.
	CB15UA	Angle: 45° Diameter 1.5mm	Supersteel Blade for cutting high-intensity reflective film or harder film.
	CB15UA-K30	Angle: 60° Diameter 1.5mm	Supersteel Blade for cutting rigid media, 0.25 mm to 0.5 mm thick. And also small detailed characters on marking film (up to 0.25mm). Recommended blade for sandblast rubber resist media cutting and Avery Series of Reflective sheeting.
	PM-CC-002	Cross Cutter Blade	Supersteel Blade

Please Refer To The Users Manual For Blade/Application Compatibility.

FC9000 SERIES BLADE HOLDERS

	PHP33-CB09N-HS SPRING BUILT-IN	Compatible with Blades: **CB09UA • CB09UA-K60 • CB09UB • CB09UB-K60** 0.9mm, blue top, black ABS tip. Not recommended for CB09UA blades with springs.
	PHP33-CB15N-HS SPRING BUILT-IN	Compatible with Blades: **CB15U • CB15U-K30* • CB15UA • CB15U-K20-2SP • CB15UA-K30 • CB15UB** 1.5mm**, red top, black ABS tip.
	PHP35-CB09-HS SPRING BUILT-IN	Compatible with Blades: **CB09UA • CB09UA-K60 • CB09UB • CB09UB-K60** 0.9mm, blue top, black brass tip. ***ATTENTION:*** *If you are using CB09UA Blade (with spring); Insert only the CB09UA blade without the spring. This blade-holder, plunger design already includes an internal spring. These brass tip blade-holders, plungers are more rigid and lend to more accurate cutting.*
	PHP35-CB15-HS SPRING BUILT-IN	Compatible with Blades: **CB15U • CB15U-K30* • CB15UA • CB15U-K20-2SP • CB15UA-K30 • CB15UB** 1.5mm**, red top, black brass tip. These brass tip blade-holders/plungers are more rigid & lend to more accurate cutting. ***NOTE:*** *REMOVE CB15 SP Blade spring before installing into this Blade-holder. DO NOT install any blade spring to more accurate cuts.*
	PHP34-BALL	Ballpoint pen holder for black, oil based pen (KB700-BK).
	PHP71-SHARPIE	Sharpie Pen holder with a metal sleeve that can be used with our FC & CE Cutters

*** Suitable for a rigid media, 0.25 mm to 0.5 mm thick or cutting small detailed characters on marking film (up to 0.25mm).**
**** Require to remove spring.**

Recommended Setting On Control Panel: CB15U-K30 **Offset** +2, **Force** 10-14, **Speed** 30 or less, **Acceleration** 4